

norpro[®]

A Global Power Solutions Company

Navigator Series

marine generator family by **norpro**

Model **4NI** 4.3kW


Main Specifications

AC Output.....4.3kW, 60Hz, 3600RPM, 1 Ph, 120/240V
Voltage Regulation (Marathon).....+5%

Engine: Farymann Diesel Model 18W

Type.....1 cyl., 4 cycle, water cooled, OHV
Fuel System.....Indirect injection
Bore & Stroke (mm).....82 x 55
Piston Displacement.....290cc
Compression Ratio.....20:1
Coolant Capacity (Block qts.).....8
Lube Oil Capacity (qts.).....1.057
dB(A) @ 7 meter w/o intake & exhaust attenuated.....87
dB(A) @ 7 meter w/sound shield & muffler.....57
Fuel Consumption at full load.....1.5 pph
Warranty.....1 year 1000 hour

EPA Certified



(Some options may be shown)

Standard Features

Starter.....12V
Exhaust Manifold.....Water Cooled
Oil Pan.....30° Inclination All Directions
Auto Shutdown.....Low Oil Pressure/High Water Temp
Harness Extension.....10 Foot
Panel w/ Gauges.....Remote Mount
Paint Color.....Ultra White

Generator Standard Features

- Internal regulator system incorporates capacitor circuit to best meet user needs
- Maximum 5% or better voltage deviation
- Brushless design minimizes maintenance and service costs
- Manufactured with class "F" or better insulation as defined by applicable NEMA standard
- Body rigidly coupled to the engine
- Single piece two pole rotor lamination for strength and lasting durability
- Direct drive centrifugal blower
- Single phase
- **1 year/unlimited hour warranty**

Complete teardown in only 10 minutes; 2 removable access panels provide an easy and accessible work area

Powder coated gloss white aluminum sound shield

State of the art design with a world class finish.



Connection holes make for a neat and clean installation.

Full sound abatement with an amazing 57 db(A) noise level at full load.

Delivering excellence one generator at a time

MODEL 4NI

Standard




Optional



Optional Equipment

- Extension plug-in wiring harnesses in 5', 10', 20' and 50' lengths
- Dual station plug-in instrument panel with "Y" harness
- Buddy Box (see going spare parts kit)
- Engine sound enclosure



MODEL	LENGTH	WIDTH	HEIGHT	DRY WEIGHT	ENCLOSURE (LxWxH)
4NI	28"	14"	18.5"	129 lbs	31.7"x16"x19"
6NI	30"	20"	22"	379 lbs	35.6"x23"x25"
9NI	32"	20"	22"	446 lbs	35.6"x23"x25"
12NI	35.5"	20"	24.5"	527 lbs	39.5"x23"x26"
14NI	35.5"	20"	24.5"	539 lbs	39.5"x23"x26"
18NI	37"	20"	25.5"	596 lbs	45.5"x23"x26"
21NI	42"	20"	25.5"	742 lbs	45.5"x23"x26"
30NI	50"	25"	33"	934 lbs	N/A
40NI	59"	25"	36"	1526 lbs	N/A
60NI	68"	25"	38"	1900 lbs	N/A
84NI	68"	25"	38"	2180 lbs	N/A
99NI	68"	25"	38"	2810 lbs	N/A
120NI	68"	25"	38"	2850 lbs	N/A

Authorized Sales & Service Dealer